Range: The largest possible range results of an optimum installation of the receiver antenna, aimed transmission in direction of the receiver, free of obstacles, with high position of transmitter and actuation of transmitter button for at least 1-2 seconds

The range you can reach at the individual place of usage depends on receiver- and transmitter position, as well as on the installation of the receiver antenna. The range may vary during rain, fog, snow and local disturbances.

Self-help at malfunctions

a) Wrong kind of transmitter?

Transmitter and receiver not compatible does the keypad have the correct colour?

b) LED doesn't work

- Insert a new battery
- Recycle empty batteries.
 Battery inserted wrong way round?

c) Range too low

- Check or change installation of antenna at receiver.
- Change operating position of transmitter.
- Check battery of transmitter.

Cleaning: The cover may be cleaned with a moisturized cloth. The inside of the transmitter may not become wet. Warning notes: Store transmitters out of children's reach (risk of suffocation through

small parts, risk of injury through unintended operation of the gate facility). **If a battery is** swallowed by a child immediately call

Don't use the transmitters in explosion hazardous areas and also in areas, where the

usage of radio systems is forbidden.
The Tousek transmitters may only be used for devices and facilities, where no danger for persons or things arises from a malfunction of transmitter or receiver

The remote controlling of devices and plants with an increased accident risk (e.g. crane facilities) is forbidden!

At operation in vehicles, don't store the transmitters exposed to sunlight.

Always store the transmitters stable

Falling down may lead to damages or a decreased transmitting range. Don't store or actuate transmitters in wetness, damp, high humidity, dust or direct solar radiation.

Changing battery: After opening the transmitter replace the old battery by a new one (only type CR2032). Please note that the plus pole (+) is on top. Used batteries should not be placed in the household waste!

ϵ

The company Tousek declares, that the transmitters

RS 868 type TXR868A01F-02F-04F comply with guideline R&TTE 1999/5/CE.

A copy of the declaration of conformity is available at www.tousek.at/ce. The device is approved for usage in all EUmember states

EN RS-868-TXR-Handsende 80302602

EN RS-868-

TXR-Handsender 80302602

(managing director)

≜ ≥ tousek

Transmitter Typ RS 868-TXR Additional Instructions



Range: The largest possible range results of an optimum installation of the receiver antenna, aimed transmission in direction of the receiver, free of obstacles, with high position of transmitter and actuation of transmitter button for at least 1-2 seconds.

The range you can reach at the individual place of usage depends on receiver- and transmitter position, as well as on the installation of the receiver antenna. The range may vary during rain, fog, snow and local disturbances.

Self-help at malfunctions

a) Wrong kind of transmitter?

 Transmitter and receiver not compatible. oes the keypad have the correct colour?

b) LED doesn't work

- Insert a new battery.
- Recycle empty batteries. Battery inserted wrong way round?

c) Range too low

- Check or change installation of antenna at receiver.
- Change operating position of transmitter.
- Check battery of transmitter.

Cleaning: The cover may be cleaned with a moisturized cloth. The inside of the transmitter may not become wet.

Warning notes: Store transmitters out of children's reach (risk of suffocation through small parts, risk of injury through unintended operation of the gate facility). **If a battery is** swallowed by a child immediately call

Don't use the transmitters in explosion hazardous areas and also in areas, where the usage of radio systems is forbidden.

The Tousek transmitters may only be used for devices and facilities, where no danger for persons or things arises from a malfunction of transmitter or receiver.

The remote controlling of devices and plants with an increased accident risk (e.g. crane facilities) is forbidden!

At operation in vehicles, don't store the transmitters exposed to sunlight.

Always store the transmitters stable.

Falling down may lead to damages or a decreased transmitting range. Don't store or actuate transmitters in wetness, damp, high humidity, dust or direct solar radiation. Changing battery: After opening the transmitter replace the old battery by a new one (only type CR2032). Please note that the plus pole (+) is on top. Used batteries should not be placed in the household waste!

ϵ

The company Tousek declares, that the transmitters

RS 868 type TXR868A01F-02F-04F comply with guideline R&TTE 1999/5/CE.

A copy of the declaration of conformity is available at www.tousek.at/ce.

The device is approved for usage in all EU-





Transmitter Typ RS 868-TXR Additional Instructions



Range: The largest possible range results of an optimum installation of the receiver antenna, aimed transmission in direction of the receiver, free of obstacles, with high position of transmitter and actuation of transmitter button for at least 1-2 seconds

The range you can reach at the individual place of usage depends on receiver- and transmitter position, as well as on the installation of the receiver antenna. The range may vary during rain, fog, snow and local disturbances

Self-help at malfunctions

a) Wrong kind of transmitter?

Transmitter and receiver not compatible, does the keypad have the correct colour? b) LED doesn't work

Insert a new battery.

Recycle empty batteries.
Battery inserted wrong way round?

- c) Range too low
 Check or change installation of antenna at receiver.
 - Change operating position of transmitter.
 Check battery of transmitter.

Cleaning: The cover may be cleaned with a moisturized cloth. The inside of the transmitter may not become wet.

Warning notes: Store transmitters out of children's reach (risk of suffocation through small parts, risk of injury through unintended operation of the gate facility). If a battery is swallowed by a child immediately call

Don't use the transmitters in explosion hazardous areas and also in areas, where the usage of radio systems is forbidden.

The Tousek transmitters may only be used for devices and facilities, where no danger for persons or things arises from a malfunction of transmitter or receiver.

The remote controlling of devices and plants with an increased accident risk (e.g. crane facilities) is forbidden!

At operation in vehicles, don't store the transmitters exposed to sunlight.

Always store the transmitters stable

Falling down may lead to damages or a decreased transmitting range. Don't store or actuate transmitters in wetness, damp, high humidity, dust or direct solar radiation.

Changing battery: After opening the transmitter replace the old battery by a new one (only type CR2032). Please note that the plus pole (+) is on top. Used batteries should not be placed in the household waste!

(€

The company Tousek declares, that the transmitters

RS 868 type TXR868A01F-02F-04F comply with guideline R&TTE 1999/5/CE.

A copy of the declaration of conformity is available at www.tousek.at/ce

The device is approved for usage in all EUmember states

EN RS-868-TXR-Handsender 80302602

EN RS-868-

80302602

TXR-Handsender

Eduard Tousek (managing director)



Transmitter Typ RS 868-TXR Additional Instructions



Range: The largest possible range results of an optimum installation of the receiver antenna, aimed transmission in direction of the receiver, free of obstacles, with high position of transmitter and actuation of transmitter button for at least 1-2 seconds

The range you can reach at the individual place of usage depends on receiver- and transmitter position, as well as on the installation of the receiver antenna. The range may vary during rain, fog, snow and local

Self-help at malfunctions

a) Wrong kind of transmitter?

 Transmitter and receiver not compatible. does the keypad have the correct colour?

b) LED doesn't work Insert a new battery

- Recycle empty batteries. Battery inserted wrong way round?

c) Range too low

- Check or change installation of antenna at receiver.
- Change operating position of transmitter. - Check battery of transmitter

Cleaning: The cover may be cleaned with a moisturized cloth. The inside of the transmitter may not become wet.

Warning notes: Store transmitters out of children's reach (risk of suffocation through small parts, risk of injury through unintended operation of the gate facility). If a battery is swallowed by a child immediately call

Don't use the transmitters in explosion hazardous areas and also in areas, where the usage of radio systems is forbidden.
The Tousek transmitters may only be used

for devices and facilities, where no danger for persons or things arises from a malfunction of transmitter or receiver.

The remote controlling of devices and plants with an increased accident risk (e.g. crane facilities) is forbidden! At operation in vehicles, don't store the trans-

mitters exposed to sunlight. Always store the transmitters stable

Falling down may lead to damages or a decreased transmitting range. Don't store or actuate transmitters in wetness, damp, high humidity, dust or direct solar radiation.

Changing battery: After opening the transmitter replace the old battery by a new one (only type CR2032). Please note that the plus pole (+) is on top. Used batteries should not be placed in the household waste!

ϵ

The company Tousek declares, that the

RS 868 type TXR868A01F-02F-04F comply with guideline R&TTE 1999/5/CE

A copy of the declaration of conformity is available at www.tousek.at/ce. The device is approved for usage in all EU-

member states

Eduard Tousek (managing director)




≜ ≥ tousek

Transmitter Typ RS 868-TXR Additional Instructions

Transmitters RS 868-TXR:

This manual is an addition to the according installation- and operating instructions "Rolling code radio system RS868"
For storing transmitters in the shutter controls PRT868, PRT868 mini, PRF868 r the radio

light switch RRL868, see according receiver instructions



on P3

The receiver checks the incoming transmitter signal on correct encoding before forwarding the command. Thus, the transmitter button has to be presses for approx. 1 -2 seconds.

Memorizing of new transmitters through an already stored transmitter:

Attention at multi-channel facilities:

The power supply for possibly existing additional receivers has to be turned off, to avoid an unintentional activation of several receivers during memorizing.

- 1. For memorizing transmitters you have to be in the immediate near of your radio receiver (which is external or installed in the control unit).
- 2. Open the cover of the already memorized transmitter: Hold the cover of the transmitter between thumb and forefinger and press the cover together and upwards.



3. Through pressing the white memorizing button P3, the receiver is set in memorizing mode and emits a 5 s long continuous tone As soon as you hear this tone, release button P3

within 5 seconds

- 4. Within these 5 s now press the channel button which should be stored. Hold the channel button until you can hear several successive signals (the channel has been successfully stored in the receiver memory).
- 5. Now memorizing is finished. Please test if the new transmitter works correctly through

pressing the stored channel button. For memorizing further transmitters, please repeat the whole procedure.

If the receiver memory is full, a continuous beep-tone is emitted.

Attention:


If the transmitter isn't stored in the receiver, this may have the following reasons:

- a) receiver memory full (84 different codes possible) b) receiver has not been activated for storage through transmitter.
- c) transmitter and receiver not compatible (does keypad have the correct colour?)

Transmitters RS 868-TXR

This manual is an addition to the according installation- and operating instructions "Rolling code radio system RS868"

For storing transmitters in the shutter controls PRT868, PRT868 mini, PRF868 r the radio light switch RRL868, see according receiver instructions



rizina button P3 coin cell 3V (CR2032)

The receiver checks the incoming transmitter signal on correct encoding before forwarding the command. Thus, the transmitter button has to be presses for approx. 1 -2


Memorizing of new transmitters through an already stored transmitter:

Attention at multi-channel facilities:

The power supply for possibly existing additional receivers has to be turned off, to avoid an unintentional activation of several receivers during memorizing.

- 1. For memorizing transmitters you have to be in the immediate near of your radio receiver (which is external or installed in the
- 2. Open the cover of the already memorized transmitter: Hold the cover of the transmitter between thumb and forefinger and press the cover together and upwards.





3. Through pressing the white memorizing button P3, the receiver is set in memorizing mode and emits a 5 s long continuous tone. As soon as you hear this tone, release

button P3. 4. Within these 5 s now press the channel button which should be stored. Hold the channel button until you can hear several successive signals

(the channel has been successfully stored in the receiver memory). 5. Now memorizing is finished. Please test if the new transmitter works correctly through

pressing the stored channel button. For memorizing further transmitters, please repeat the whole procedure.

If the receiver memory is full, a continuous

beep-tone is emitted.

Attention:

If the transmitter isn't stored in the receiver, this may have the following reasons:


a) receiver memory full (84 different codes possible) b) receiver has not been activated for storage through transmitter.

c) transmitter and receiver not compatible (does keypad have the correct colour?)

Transmitters RS 868-TXR:

This manual is an addition to the according installation- and operating

instructions "Rolling code radio system RS868"
For storing transmitters in the shutter controls PRT868, PRT868 mini, PRF868 r the radio light switch RRL868, see according receiver



rizina button P3 coin cell 3V (CR2032)

The receiver checks the incoming transmitter signal on correct encoding before forwarding the command. Thus, the transmitter button has to be presses for approx. 1 -2

Memorizing of new transmitters through an already stored transmitter:

Attention at multi-channel facilities:

The power supply for possibly existing additional receivers has to be turned off, to avoid an unintentional activation of several receivers during memorizing.

- 1. For memorizing transmitters you have to be in the immediate near of your radio receiver (which is external or installed in the control unit).
- 2. Open the cover of the already memorized transmitter: Hold the cover of the transmitter between thumb and forefinger and press the cover together and upwards.



within 5 seconds pressing the stored channel button. For me-

- $\begin{tabular}{ll} \bf 3. & Through & pressing the white memorizing \\ button & {\bf P3}, & the receiver is set in memorizing \\ \end{tabular}$ mode and emits a 5 s long continuous tone As soon as you hear this tone, release button P3.
- 4. Within these 5 s now press the channel button which should be stored. Hold the channel button until you can hear several successive signals (the channel has been successfully stored in the receiver memory).
- 5. Now memorizing is finished. Please test if the new transmitter works correctly through

morizing further transmitters, please repeat the whole procedure.

If the receiver memory is full, a continuous beep-tone is emitted.

Attention:


If the transmitter isn't stored in the receiver, this may have the following reasons:

- a) receiver memory full (84 different codes possible)
 b) receiver has not been activated for storage through transmitter.
- c) transmitter and receiver not compatible (does keypad have the correct colour?)

Transmitters RS 868-TXR:

This manual is an addition to the according installation- and operating instructions "Rolling code radio system RS868"
For storing transmit

For storing transmitters in the shutter controls PRT868, PRT868 mini, PRF868 r the radio light switch RRL868, see according receiver instructions.



rizina button P3 coin cell 3V (CR2032)

The receiver checks the incoming transmitter signal on correct encoding before forwarding the command. Thus, the transmitter button has to be presses for approx. 1 -2


Memorizing of new transmitters through an already stored transmitter:

Attention at multi-channel facilities:

The power supply for possibly existing additional receivers has to be turned off, to avoid an unintentional activation of several receivers during memorizing.

- 1. For memorizing transmitters you have to be in the immediate near of your radio receiver (which is external or installed in the
- 2. Open the cover of the already memorized transmitter: Hold the cover of the transmitter between thumb and forefinger and press the cover together and upwards





- 3. Through pressing the white memorizing button **P3**, the receiver is set in memorizing mode and emits a 5 s long continuous tone. As soon as you hear this tone, release button P3.
- 4. Within these 5 s now press the channel button which should be stored. Hold the channel button until you can hear several successive signals (the channel has been successfully stored in the receiver memory).
- 5. Now memorizing is finished. Please test if the new transmitter works correctly through

pressing the stored channel button. For memorizing further transmitters, please repeat the whole procedure.

If the receiver memory is full, a continuous

beep-tone is emitted.

Attention:

If the transmitter isn't stored in the receiver, this may have the following reasons:

a) receiver memory full (84 different codes possible) b) receiver has not been activated for storage through transmitter.

c) transmitter and receiver not compatible (does keypad have the correct colour?)